



GRANDSTREAM
CONNECTING THE WORLD



6-line Carrier-Grade IP Phone

GRP2613(W)


The GRP2613 is a powerful 6-line carrier-grade IP phone designed with zero-touch provisioning for mass deployment and easy management. It features a sleek design and a suite of next-generation features including 24 virtual multi-purpose keys (VPKs), integrated Wi-Fi (GRP2613W), dual Gigabit ports, a color LCD with swappable face plates for easy logo customization and more. The GRP series includes carrier-grade security features to provide enterprise-level security, including secure boot, dual firmware images and encrypted data storage. For cloud provisioning and centralized management, the GRP2613 is supported by Grandstream's Device Management System (GDMS), which provides a centralized interface to configure, provision, manage and monitor deployments of Grandstream endpoints. Built for the needs of desktop workers and designed for easy deployment by enterprises, service providers and other high-volume markets, the GRP2613 offers an easy-to-use and easy-to-deploy voice endpoint.



Supports up to 4 SIP accounts (GRP2613), 6 SIP accounts (GRP2613W) and 6 multi-purpose line keys



Dual switched auto-sensing 10/100/1000 Mbps Gigabit ethernet ports with integrated PoE



Swappable faceplate to allow for easy logo customization



Equipped with noise shield technology to minimize background noise



HD audio supporting all major codecs, including wideband codecs G.722 and Opus



Up to 24 digital BLF keys



Integrated dual-band (2.4GHz and 5GHz) Wi-Fi 6 (802.11a/b/g/n/ac/ax) and Bluetooth® (GRP2613W only)



Enterprise-level protection including secure boot, dual firmware images, and encrypted data storage

Protocols/Standards	SIP RFC3261, TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP, ICMP, DNS(A record, SRV, NAPTR), DHCP, PPPoE, TELNET, TFTP, NTP, STUN, SIMPLE, LLDP, LDAP, TR-069, 802.1x, TLS, SRTP, IPV6
Network Interfaces	Dual switched auto-sensing 10/100/1000 Mbps Gigabit Ethernet ports with integrated PoE
Wi-Fi	GRP2613W, Integrated dual-band (2.4GHz and 5GHz) Wi-Fi 6 (802.11a/b/g/n/ac/ax)
Bluetooth®	GRP2613W, Integrated
Graphic Display	2.8 inch (320x240) TFT color LCD
Feature Keys	6 line keys with up to 4 (GRP2613) or 6 (GRP2613W) SIP accounts, 4 XML program-mable context sensitive softkeys, 5 navigation/menu keys, 11 dedicated function keys for: MESSAGE(with LED indicator), PHONEBOOK, TRANSFER, CONFERENCE, HOLD, HEADSET, MUTE, SEND/REDIAL, SPEAKERPHONE, VOL+, VOL-
Auxiliary Port	RJ9 headset jack (allowing EHS with Plantronics headsets)
Voice Codecs and Capabilities	Support for G7.29A/B, G.711µ/a-law, G.726, G.722(wide-band), G723, iLBC, OPUS, in-band and out-of-band DTMF(in audio, RFC2833, SIP INFO), VAD, CNG, AEC, PLC, A/B, AGC
Telephony Features	Hold, transfer, forward, 5-way conference, call park, call pickup, shared-call-appearance(SCA)/bridged-line-appearance(BLA), downloadable phonebook(XML, LDAP, up to 1000 items), call waiting, call log (up to 2000 records), XML customization of screen, off-hook auto dial, auto answer, click-to-dial, flexible dial plan, hot-desking, personalized music ringtones and music on hold, server redundancy and fail-over
HD Audio	Yes, HD handset and speakerphone with support for wideband audio
Base Stand	Yes, 2 angle positions available, Wall Mountable (Wall Mount *sold separately)
QoS	Layer 2 QoS (802.1Q, 802.1P) and Layer 3 (ToS, DiffServ, MPLS) QoS
Security	User and administrator level passwords, MD5 and MD5-sess based authentication, 256-bit AES encrypted configuration file, SRTP, TLS, 802.1x media access control, secure boot.
Multi-language	English, German, Italian, French, Spanish, Portuguese, Russian, Croatian, Chinese, Korean, Japanese, and more
Upgrade/Provisioning	Firmware upgrade via FTP/TFTP/TFTPS/HTTP/HTTPS, mass provisioning using GDMS/TR-069 or AES encrypted XML configuration file.
Power & Green Energy Efficiency	Universal power adapter included: Input:100-240V ; Output: +5V, 0.6A ; Integrated Power-over-Ethernet(802.3af) IEEE 802.3az Energy-Efficient Ethernet Max power consumption 3W(power adapter) or 3.8W(PoE)
Temperature and Humidity	Operation: 0°C to 40°C Storage: -10°C to 60°C Humidity: 10% to 90% Non-condensing
Package Content	GRP2613 phone, handset with cord, phone stand, 5V power adapter, network cable, Quick Installation Guide, GPL license
Physical	Dimension: 203mm x 193mm x 52.1mm; Unit weight: 554g ; Package weight: 936g
GRP2613 Compliance	FCC: Part 15 Class B; FCC Part 68 HAC CE: EN 55032; EN 55035; EN 61000-3-2; EN 61000-3-3; EN 62368-1 RCM: AS/NZS CISPR32;AS/NZS 61000.3.2; AS/NZS 61000.3.3;AS/NZS 62368.1; AS/CA S004 IC: ICES-003; CS-03
GRP2613W Compliance	CE: ETSI EN 300 328;ETSI EN 301 893; EN 300 440; ETSI EN 301 489-1/-3/-17; EN IEC 62368-1; EN 55032; EN 55035; EN IEC 61000-3-2; EN 61000-3-3; EN IEC 62311 FCC: Part 15 Subpart B, Class B; Part 15 Subpart E, 15.407; Part 15 Subpart C, 15.247; FCC Part 68 IC: RSS-247 Issue 2; RSS-Gen Issue 5; ICES-003 Issue 7; ISED CS-03 Part V RCM:AS/NZS CISPR32; AS/NZS 4268; AS/NZS 2772.2; AS/NZS 62368.1; AS/CA S004